Product datasheet

Specifications



Push Button Mechanism, Impress Series, Intermediate, 230/240V, 16A/10AX

30PBI-WE

Main

Range of product	Series 30 Impress
Product or component type	Push-button
Product brand	Clipsal
Device presentation	Basic element

Complementary

Colour code	WE
Actuator	Push-button
Local signalling	Without light indicator
Material	Plastic
[Ue] rated operational voltage	250 V AC
Inrush current	16 A
Depth	10 mm
Width	21 mm
Length	21 mm
Load type	LEDi lamp 100 W Fluorescent lamp 10 AX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	2.5 cm
Package 1 Length	4.5 cm
Package 1 Weight	25 g

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

More information about methodology >

Environmental footprint

Total lifecycle Carbon footprint	**0 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**4 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Halogen free product**
PVC free	**Product contains PVC**

Use Again

Repack and remanufacture

Recyclability potential, in %	**15**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**