Product datasheet

Specifications



Double Switch Power Point, Clipsal Iconic, Horizontal Mount, 250V, 10A

3025-VW

Main

Range	Clipsal Iconic
Product or component type	Switched socket
Device presentation	Complete product
Number of Switched socket	2
Colour tint	Vivid white
Connections - terminals	Screw terminals

Complementary

Installation direction	Horizontal
Device mounting	Flush
Number of Switch	2
Rated current	10 A
[Ue] rated operational voltage	230/240 V
Outlet poles configuration	2P + E
fixing mode	By screws
Material	PC (polycarbonate)
Clamping connection capacity	1 x 2.5...4 x 2.5 mm² for rigid cable(s) 1 x 2.5...4 x 2.5 mm² for stranded cable(s) 1 x 2.5...4 x 2.5 mm² for flexible cable(s)
Surface finish	Matt
surface treatment	Untreated
Wire stripping length	16 mm
Net weight	116 g

Environment

Ambient air temperature for operation	0…45 °C

Dimensions

Height	78 mm
Width	120 mm
Depth	27 mm

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	8 cm
Package 1 Length	12 cm
Package 1 Weight	121 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	150 cm
Package 2 Width	106 cm
Package 2 Length	330 cm
Package 2 Weight	1.33 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**11 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**9 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.3 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Halogen free product**
PVC free	**Product contains PVC**
Silicone-free	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**43**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**