Product datasheet

Specifications



Double Power Point with Dual USB Charger, Clipsal Iconic, Horizontal Mount, 250V, 10A

3025USB2-VW

Discontinued on: 30 Sept 2026

To be discontinued

Main

Range	Clipsal Iconic
Product or component type	Switched socket with USB charger
Type of USB power supply	USB type A
Integrated connection type	2 socket-outlet 220/230/240 V AC, maximum load current: 10 A 2 USB type A 5 V DC, maximum load current: 3.1 A
Number of power socket outlets	2
Colour tint	Vivid white
Type of packing	Polybag
Quantity per set	Set of 10
Switch function	With ON/OFF function

Complementary

Device presentation	Complete product
Number of rocker	2
Device mounting	Flush
Installation direction	Horizontal
Control type	ON/OFF button
Rated current	10 A
[Ue] rated operational voltage	220...240 V
Connections - terminals	screw terminals
Clamping connection capacity	1 x 2.5...4 x 2.5 mm² for stranded cable(s) 1 x 2.5...4 x 2.5 mm² for flexible cable(s) 1 x 2.5...4 x 2.5 mm² for rigid cable(s)
fixing mode	By screws
Surface finish	Matt
Wire stripping length	16 mm
Height	78 mm
Width	120 mm
Depth	55 mm

Environment

Ambient air temperature for storage	0…60 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	0…45 °C
Relative humidity	10…95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	6.6 cm
Package 1 Length	15.2 cm
Package 1 Weight	200 g

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**13 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**11 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.5 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Product contains halogen above thresholds**
PVC free	**PVC-free product**

Use Again

Repack and remanufacture

Recyclability potential, in %	**43**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative

